VOYAGER LATHE

• Includes 2 Axis Digital Readout



SPECIFICATION

| Max.Swing over Bed | 356mm |
|-------------------------------|---|
| Max. Swing over Carriage | 210mm |
| Max Swing over Gap | 508mm |
| Width of Bed | 260mm |
| Distance Between Centers | 750mm/1000mm |
| Taper of Spindle Bore | MT5 |
| Diameter of Spindle Bore | 40mm |
| Number of Spindle Speeds | 12 |
| Range of Spindle Speeds | 40-1800rpm |
| Spindle Nose | D 1-4 |
| Metric Threads | 37kinds / (0.4-7mm) |
| | 23kinds / (0.45-7.5mm) |
| Whitworth Threads | 28kinds / (4-56T.P.I) 40kinds / (4-112T.P.I) |
| | |
| Range of Longitudinal Feeds | 0.043-0.653 |
| Range of Cross Speeds | 0.024-0.359 |
| Diameter of Leadscrew | 22mm |
| Pitch Threads of Leadscrew | 4mm or 8T.P.I |
| Travel of Tailstock Quill | 120mm |
| Diameter of Tailstock Quill | 45mm |
| Taper Hole of Tailstock Quill | MT3 |
| Main Motor Power | 2.4KW,3HP,60Hz,230V |
| Coolant Pump Motor Power | 0.04kw |
| Overall Dimensions | 1900mm x710mm x1170mm |
| Net Weight | 1200kg |
| Stock Code 750mm | LAT-VOY-750 |
| Stock Code 1000mm | LAT-VOY-1000 |
| Price ex vat 750mm | £4,850.00 |
| Price ex vat 1000mm | £4,970.00 |

FEATURES

- Removable Swarf Tray
- Large Range of Speeds
- Rigid Construction
- Optional Taper Turning Attachment
- Bed Stop
- Jog Facility

STANDARD ACCESSORIES

- 200mm 3-Jaw Chuck
- 200mm 4-Jaw Chuck
- Live Centre
- Fixed Steady
- Travelling Steady
- Coolant System
- Halogen Work Light
- Manual & Parts List
- Accuracy Report
- Camlock Spindle
- 2 Axis Digital Readout



OPTIONAL ACCESSORIES



Backplate 200mm



5/8" Indexable Lathe Tools



Centring Chuck

Soft Jaws for 160mm 3-Jaw Chuck



Quick Change Toolpost + 5 Holders



Vertical Slide