C300 LATHE



SPECIFICATION

| Model | C300 |
|-------------------------------|--------------|
| Swing over Bed | 330mm |
| Swing over Cross Slide | 210mm |
| Swing in Gap | 480mm |
| Distance between Centers | 1000mm |
| Spindle Nose | D1-4 |
| Taper in Spindle Nose | MT3 |
| Spindle Bore | 40mm |
| Spindle Speed Range | 40-2500rpm |
| Spindle Speeds | 12 |
| Maximum Spindle Potor Power | 2.2 KW |
| Number of Imperial Pitches | 52 |
| Range of Imperial Pitches | 2 to 56 TPI |
| Number of Diametral Pitches | 18 |
| Range of Diametral Pitches | 8 to 56 DP |
| Number of Metric Pitches | 45 |
| Range of Metric Pitches | 0.2 to 14 mm |
| Number of Module Pitches | 18 |
| Range of Module Pitches | 0.3 to 3.5 |
| Tailstock Quill Taper | 3 MT |
| Tailstock Quill Travel | 110mm |
| Width of Guideway | 205mm |
| Cross Slide Travel - X Travel | 190mm |
| Travel of Top Slide | 92mm |
| Overall Machine Weight | 790kg |
| Stock code | LAT-C300 |
| Price ex va | £7,902.32 |

STANDARD ACCESSORIES

- 200mm 3-Jaw Chuck
- 200mm 4-Jaw Chuck
- Live Centre
- Fixed Steady
- Travelling Steady
- Coolant System
- Halogen Work Light
- Manual & Parts List
- Accuracy Report Camlock Spindle
- 2 Axis Digital Readout

FEATURES

- Camlock Spindle Nose
- Wide Cross Slide For High Stability During Heavy Cutting
- Hardened And Ground V Bed Ways
- Nvr Protection
- Torque Protection On Leadscrew And Feed Rod
- Foot Brake
- Safety Lock On Electric Cabinet
 - Metric, Imperial, Mp And Dp Thread Cutting
- Strong Chuck Guard Switched to Stop Machine Automatically



1

Live centre MT3

OPTIONAL ACCESSORIES









5

Quick Change Toolpost + 5 Holders

Drill Chuck & Arbor

Vertical Slide

5/8" Indexable Lathe Tools

1-13mm

7